

PRODUCT NAME

OXYD

PRODUCT DESCRIPTION

Oxyd is a ready-to-use decorative compound to create a rust effect.

APPLICATION

Interior wall decoration for residential, office and public spaces. Can be used on a variety of substrates including plasterboard, cement-lime plaster, previously painted surfaces, etc.

SUBSTRATE PREPARATION

The substrate should be dry, clean and durable. Remove any damaged (e.g. flaking and cracked) coating of previous paints, adhesive and lime paints. Fill surface defects with a suitable filler and sand down. Clean previously painted surfaces of all impurities that hinder paint adhesion, e.g. dust, greasy stains, rust, fungus and mould. Apply Oxyd Primer to the surface according to the instructions on the packaging. Allow to dry for approx. 4 hrs.

PRODUCT PREPARATION

- ✓ The product should be mixed thoroughly before use.
- ✓ Do not mix the paint with other paints.
- ✓ Do not dilute with water
- ✓ Prepare Oxyd Primer and Oxyd activator.

APPLICATION

Methods: trowel

Apply the first thin layer with a trowel, spreading the product in all directions. Allow to dry for approx. 8h. After this time, apply the second coat in the same way as the first, so that there are no visible penetrations to the substrate. Apply at a temperature of +8°C to +25°C, at a relative humidity of max. 82%, avoiding draughts. Allow to dry for approx. 8 hrs. After this time, spray **Oxyd with activator**. The rust effect will appear between 2-8h. You can repeat the rust formation process until you achieve the desired effect. After a minimum of 24 h after spraying Oxyd activator, apply **Jeger Oxyd Protector**, which stops the activation process and protects the decorated surface. After painting, wash the painting tools with warm water.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 21.03.2022

Remember: You can repeat the rust activation process several times until you achieve the desired effect. The product is intended for interior use.

DRYING TIME

At +23°C and 50% relative humidity, the coating is dry to the touch after approx. 8 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

EFFICIENCY

up to 6m²/L- Practical performance depends on factors such as: type, absorbency and texture of the substrate and method.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1L

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25°C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains 1,2-benzisothiazolin-3-one, a post-reaction mixture of 5- chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) and 2- methylisothiazol-3(2H)-one. May cause an allergic reaction. Seek medical advice if necessary. Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC content limit (Cat. A/L/FW) per package 200g/L (2010). This product contains less than 1g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 21.03.2022