

PRODUCT NAME

Primer Onyx

PRODUCT DESCRIPTION

Jeger Primer Onyx is a primer for use under the Jeger Onyx effect. It ensures proper application and that the desired colour is achieved.

APPLICATION

The product is designed to be applied to surfaces prior to the application of Jeger Onyx.

SUBSTRATE PREPARATION

Previously painted surfaces should be cleaned of impurities that limit paint adhesion, e.g. dust, greasy stains, rust, fungus and mould. The substrate should be dry, clean and durable. Damaged (e.g. flaking and cracked) coatings of previous paints, adhesive and lime paints should be removed. Fill surface defects with a suitable filler.

PRODUCT PREPARATION

- ✓ Primer should be mixed thoroughly before use.
- ✓ Do not mix with other paints.
- ✓ The possibility of colour efflorescence appearing on the surface of the paint is a natural feature of the product.
- ✓ If several packs from different production batches are used, they should be mixed in a larger pack to prevent differences in colour shades.

APPLICATION

Methods: roller

Apply the primer with a roller. Apply at +8°C to +25°C, relative humidity max. 82%, avoid draughts. Leave to dry for approx. 2-4 hours. Apply primer carefully and evenly. Apply in all directions with the last stroke in the same direction.

If necessary, apply another coat after approximately 2 hours. Allow to dry for 2-4 hours. After this time, the surface can be covered with a decorative effect. Wash the tools with warm water after painting.

DRYING TIME

At +23°C and 50% relative humidity, the paint is dry to the touch after approx. 2 hours. Subsequent coats should be applied after 2-4 hours. Low temperatures, increased humidity and poor ventilation prolong the drying time.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.09.2022

TECHNICAL SPECIFICATIONS

Volatile Organic Compounds (VOCs) in the container EU Directive 2004/42	Category II/Ag: EU limit value: 200 g/l (2010) This product contains less than than 36 g/l VOC
Density 20°C [g/cm ³].	1,35±2%
Degree of gloss PNC 81914:2002	Deep matt
Number of layers *depending on colour	2
Solvent	Water

EFFICIENCY

Up to 12m²/L in one coat.

Practical performance depends on factors such as the type, absorbency and texture of the substrates, application method and colour.

EXPIRY DATE

24 months from date of manufacture

PACKAGING

1l,

ENVIRONMENTAL PROTECTION

Do not pour product residues into the sewage system. Empty packaging and packaging with product residue that will no longer be used should be disposed of in an appropriately labelled waste container in accordance with national regulations.

STORAGE AND TRANSPORT

The product should be transported and stored in its original packaging, protected from the weather. The storage and transport temperature is between +5°C and +25^(o) °C. Expiry date and batch number on the packaging.

SECURITY

Keep out of the reach of children. This product contains tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo[4,5-d] midazol-2,5(1H,3H)-dione, 1,2-benzisothiazolin-3-one and a post-reaction mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May cause an allergic reaction. Seek medical advice if necessary.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.09.2022

Avoid inhalation of spray or mist. Work in well-ventilated areas. Wear personal protective equipment. Dispose of contents/container in appropriately labelled waste containers in accordance with national regulations. VOC limit (Cat. A/I/FW) per package 200g/L (2010). This product contains less than 36g/l VOC.

The information contained in the technical data sheet is not exhaustive and is based on laboratory tests, our knowledge and practical experience. They are intended to ensure optimum use of the product, but do not form the basis of any legal liability on the part of the manufacturer due to the impossibility of controlling application conditions. **Product quality is guaranteed by our ISO 9001 compliant production system.** We reserve the right to change the information provided without prior notice.

Update date: 22.09.2022